


응축기 / 공냉식 凝縮器 / 空冷式

Air cooled type / Fin & Tube / "L", "C" model





DCL DCC

■ 응축온도 : 50℃

Condensing temperature



Inner grooved tube



MODEL		DCL-020	DCL-030	DCC-050	DCC-075	DCC-100
구분						
전열면적 Surface Area(m ²)		23	27	49	64	80
응축열량 Capacity(kcal/h)		9,700	11,500	20,400	27,100	33,600
전동기 Motor(kW×극)		0.1×8P	0.1×8P	0.2×8P	0.4×8P	0.75×8P
송풍기 Fan(Ømm×EA)		500×1	500×1	600×1	700×1	750×1
풍 량 Air Volume(m ³ /min)		90	90	150	200	210
접속관경 Nozzles inch(mm)	IN	3/4(19.05)	3/4(19.05)	7/8(22.22)	1 1/8(28.6)	1 1/8(28.6)
	OUT	5/8(15.88)	5/8(15.88)	5/8(15.88)	3/4(19.05)	7/8(22.22)
외형크기 Dimensions(mm)	L	1250	1250	1300	1400	1600
	L"	640	640	770	905	905
	W	690	690	820	905	1002
	H	980	980	980	1080	1230
중 량 Weight(kg)		기무:62 기유:80	기무:65 기유:83	기무:75 기유:94	기무:90 기유:125	기무:110 기유:140

※규격 및 사양은 제품의 개선을 위하여 예고 없이 변경될 수 있습니다. All technical modifications reserver without engagement.